

For more information, please scan this code:





Genexis Pure E600

Pure Series

Full speed, seamless connectivity

After a home is connected to fiber, this fiber connectivity needs to be distributed throughout the home. Homes differ in shape and size and end-user require different types of services and connectivity options.

Therefore, from our Connected Home product line, we present the Pure E600.

Key features

- 802.11ax (Wi-Fi 6)
- \cdot Wi-Fi EasyMeshTM
- $\cdot\,$ 5GHz (4x4) and 2.4GHz (2x2) radio design
- · Easy setup/installation
- $\cdot\,$ EasyTouch Pairing with selected Genexis extenders
- · Analogue telephony support
- Desktop model and wall-mount compatible
- · Genexis CloudSight compatible

The Pure E600 is a versitile multiport router, with Wi-Fi 6 (5400 Mbps), Wi-Fi EasyMesh[™], 4 LAN ports and 2 voice ports. This allows for supreme connectivity for the end-user.

Turning the fiber connection into a real fiber experience.

The start for the best WiFi experience with Wi-Fi EasyMesh™

The Pure E600 is the perfect residential gateway to start, steer and create an EasyMesh network between different extenders.

Thanks to this EasyMesh Network, end-users are able to fully experience the best WiFi connectivity throughout the whole home. Its steering capabilities keep the load balance of the network in mind to steer mobile devices to the correct access point (requires additional range extenders).

Meaning that when the end-user freely walks through the home, it automatically connects to the most optimal access point at all time.

Resulting in the best possible WiFi experience for the end-user.

Product features and specifications Genexis Pure E600

General specifications

Dimensions (H x W x D) Weight approx. Power supply voltage Operating temperature Storage temperature Relative humidity 38x156x232 mm 420 g 12 Vdc ± 5% 2A 0 - 45 °C -25 - 70 °C 10% - 95%

WAN interface 1x 10/100/1000 Base-T Ethernet RJ45 port

LAN interface 4x 10/100/1000 Base-T Ethernet RJ45 ports

WLAN interface

2x2 MU-MIMO 802.11ax 2.4 GHz WiFi 4x4 MU-MIMO 802.11ax 5 GHz WiFi

Voice interface 2x FXS RJ11 ports

USB interface 1x USB 2.0 port

User interfaces

Power connector Power switch Reset button WPS button Device status LEDs for System, Uplink, Internet, Telephony and WiFi End-user web based GUI

Wireless features

Wi-Fi MultiMedia (WMM) Wi-Fi Protected Setup (WPS) Wi-Fi Security (WPA2 and WPA3) Wi-Fi EasyMesh[™] R2 DFS and Radar Detection Multiple SSID and hidden SSID Guest network SSID

Ethernet features

IPv4 and IPv6 dual IP stack VLAN (un)tagging, Q-in-Q, QoS PPPoE, L2TP, IGMPv3

Gateway features

NAT/PAT, DHCP, DNS NTP, RTSP Stateful Packet Inspection Firewall (SPIF) DMZ, uPnP, Port forwarding

Voice features

SIP based Voice-over-IP G.711 A-law / μ-law codec G.729 codec 5 REN support Line Echo Cancellation DTMF: In-band, RFC2833, SIP-Info Class 5 features

USB features

NTFS and FAT32 file system storage devices

Management and control

SNMP TR-069, TR369 TR-181, TR-104 data models Command Line Interface (CLI) WebGUI Genexis EasyWiFi app Genexis CloudSight Fail-safe firmware upgrade

Regulatory compliance

Radio Equipment Directive 2014/53/EU Energy Related Products Directive 2009/125/EC CE Safety Directive 2014/35/EU RoHS and REACH Directive 2011/65/EU ITU-T K.21 standard compliancy

Package content

Pure E600 Power supply unit Ethernet cable Quick installation guide

Genexis Pure E600 product model

| Model | Uplink WAN (Mbps) | LAN (Mbps) | | WLAN 2x2 2.4 GHz | WLAN 4x4 5.0 GHz | FXS | USB |
|-----------|-------------------|------------|-------------|---------------------|---------------------|-----|-----|
| Pure E600 | 10/100/1000 | 4x | 10/100/1000 | 11ax | 11ax | 2x | 1× |

Note: Not every listed feature may be included in the shipping product. We reserve the right to make changes of technical specifications, housing or design without prior notice.

